



# CC22

RELIABLE SOLUTION FOR AUTOMATED LINES

CC22 comes in both a table-top or ergonomic Z-configuration. The CC22 is built for high-volume Serial Production use. By design, the constant centerline crimping enables easy part-positioning.

The Z-configuration, with the crimping head and hydraulic unit all separate, makes the CC22 ideal for automatic line use. For automation it can be equipped with an optional Automatic Greasing Unit, enabling an interruption-free operation combined with long maintenance intervals and ensuring ultimate accuracy. It also has wiper seal, protecting dirt and debris from entering the cylinder.

## TECHNICAL DATA


Max crimping dia (mm) <sup>1)</sup>	54
Max crimping dia (inch) <sup>1)</sup>	2.12
Max crimping force (kN)	680
Max crimping force (tonnage)	68
Cycle time 10 mm (s) <sup>2)</sup>	1.8
Hose size ID (inch)	1 ¼
Die set series	CC22
Max opening (mm) <sup>3)</sup>	+25
Max opening without dies (mm)	109
Master die D/L (mm)	84/52
Master die D/L (inch)	3.31/2.05
Motor Power (kW/HP)	3/4.0
Oil tank volume	35 l

## DIMENSIONS (LxWxH)

Machine (mm)	597x475x722
Machine (inch)	23.6x18.8x28.4

## WEIGHT (KG/LBS)

130/246



- 1) With standard dies. Crimping range can be increased with special dies.
- 2) Theoretical with 10 mm cycle.
- 3) Maximum opening is the total die travel. Add this value to the minimum crimping diameter of the die set used. The result is the maximum opening of the machine with die set in place.

## CONTROL

ICC

## MODELS

Standard  
Z-model

## STANDARD FEATURES

Electric backstop device  
Pressure crimping ICC1  
Step crimping ICC2

## OPTIONS

QuickChange-tool  
Foot pedal  
Mechanical back stop device  
Quality control ICC3  
Graphical quality control ICC4  
Auto greasing G3  
Interface pack ETH (Communication TCP/IP & UDP)  
Bar Code Reader BCR



## DIE SET CC22

DieSetNo	D (mm)	L (mm)	Crimp. range (mm)
18315/10	10	50	10.0-12.0
18315/12	12	50	12.0-14.0
18315/14	14	50	14.0-16.0
18315/16	16	50	16.0-19.0
18315/19	19	50	19.0-23.0
18315/23	23	50	23.0-27.0
18315/27	27	50	27.0-31.0
18315/31	31	50	31.0-36.0
18315/36	36	50	36.0-41.0
18315/41	41	50	41.0-47.0
18315/47	47	50	47.0-54.0

In addition to the standard die sets, a wide range of special die sets is available on request.

FURTHER INFO ON PRODUCTS,  
PLEASE REVERT TO SPECIFIC PRODUCT CARD

FINNPOWER.FI

LILLBACKAUSA.COM