



P20HP

POWER FOR SERVICE CRIMPING


Finn-Power P20HP is hand pump operated hydraulic crimping machine for repair workshops and service van use. This hand-operated crimping machine works in places where electricity or compressed air are not available.

Available also with air pressure (AP-model).

TECHNICAL DATA	
Max. crimping dia (mm) 1)	61
Max. crimping dia (inch) 1)	2.40
Max. crimping force (kN)	1370
Max. crimping force (tonnage)	137
Hose size ID (inch)	1 ½ *
Die set series	20
Max. opening (mm) 2)	+25
Max. opening without dies (mm)	109
Master die D/L (mm)	84/80
Master die D/L (inch)	3.31/3.15
Motor Power	Hand pump
DIMENSIONS (LxWxH)	
(mm)	487x441x389
(inch)	19.2x17.4x15.4
WEIGHT (KG/LBS)	
66/146	

[ွ]ဝ 0 6 061

D-marking



increased with special dies.

Maximum opening is the total die travel. Add this value to the minimum crimping diameter of the die set used. The result is the maximum opening of the machine with die set in place.



Manual

OPTIONS

QuickChange-tool Mechanical back stop device





DIE SET 20-SERIES			
DieSetNo	D (mm)	L (mm)	Crimp. range (mm)
18013/10	10	55	10.0-12.0
18013/12	12	55	12.0-14.0
18013/14	14	55	14.0-16.0
18013/16	16	55	16.0-19.0
18013/19	19	55	19.0-23.0
18013/23	23	55	23.0-27.0
18013/27	27	70	27.0-31.0
18013/31	31	70	31.0-36.0
18013/36	36	75	36.0-41.0
18013/41	41	75	41.0-47.0
18013/47	47	85	47.0-54.0
18013/54	54	85	54.0-61.0

In addition to the standard die sets, a wide range of special die sets is available on request.



^{*} ACCORDING TO THE FITTING.